

Type **E** and **H** 25, 41, 60, 75, 90, 110 and 130 mm

O.D. range inches		O.D. range mm		No. of elements to make a ring	
min	max	min	max	E	H
8.70	10.55	221	268	2	1
10.59	12.60	269	320	3	
12.64	14.41	321	366	3	1
14.45	16.54	367	420	4	
16.57	18.31	421	465	4	1
18.35	20.87	466	530	5	
20.91	24.80	531	630	5	1
24.84	28.74	631	730	7	
28.78	32.68	731	830	8	
32.72	36.61	831	930	9	
36.65	40.55	931	1030	10	
40.59	45.63	1031	1159	11	
45.67	53.54	1160	1360	13	
53.58	62.99	1361	1600	15	
63.03	70.83	1601	1799	17	
70.87	83.07	1800	2110	20	
83.11	95.67	2111	2430	23	
97.71	112.6	2431	2860	27	
112.64	134.41	2861	3414	32	
Elements	Runner Height In.			Max Load Per Ring	
				Lbs	Kg
E/H 25	0.98			7826	3550
E./H 41	1.61			7385	3350
E/H 60	2.36			8929	4050
E/H 75	2.95			8598	3900
E/H 90	3.54			9039	4100
E/H 110	4.33			7606	3450
E/H 130	5.11			6834	3100